

USB Power Adapter

USB 适配器

AD598 8.0A Max. 40W



26.5 x 90.5 x 58 mm

AD599 8.0A Max. 40W



26.5 x 90.5 x 58 mm

■ Feature

- World Wide AC Input
- Light & Compact design
- Many kinds of protection
- MTBF Meet MIL-HDBK-217K, over 50K hours, full load, 25°C
- Suitable for Digital Camera, Mobile phone, Table PC and other IT Equipments etc.
- Energy Efficiency complied with DoE VI level
- Intelligent allocation of O.P.C

■ 特性

- 国际通用交流范围输入
- 小体积、轻巧便携
- 多种保护功能
- 平均故障间隔时间可达50K小时
- 适用于数码相机、手机、平板电脑等IT设备
- 符合能源之星六级
- 智能分配输出电流

Specification 参数		AD598	AD599
Input Characteristic	输入特性	100-240VAC 50/60Hz 1A Max.	
Inrush Current	浪涌电流	Less than 80A, 240VAC, 25°C	
Leakage Current	泄漏电流	Less than 0.25mA, at 264VAC	
Efficiency	效率	87.3% Min.	87.3% Min.
O.P.V	输出电压	5VDC	5VDC(USBx4, TYPE-Cx1)
O.P.C	输出电流	Single USB-A: 2.4A Max. Total: 8.0A Max.	Single USB-A: 2.4A Max. Type C: 3.0A Max. Total: 8.0A Max.
Power	功率	40W	40W
No-load Power Consumption	待机功耗	≤0.075W, 230VAC	
Tolerance	输出公差	±5%	
Ripple & Noise(max)	纹波与噪声	≤1%	
Short Circuit Protection	短路保护	Short at DC and No damage	
Working Temp. & Humidity	工作温湿度范围	0°C ~ 40°C, 5% ~ 90% RH Non-Condensing(无凝露)	
Storage Temp. & Humidity	存储温湿度范围	-20°C ~ 85°C, 5% ~ 90% RH Non-Condensing(无凝露)	
Altitude	海拔高度	Less than 3000m	
Withstand Voltage	绝缘耐压	3000VAC, 1 minute, 10mA Max.	
Insulation Resistance	绝缘阻抗	Input to Output: ≥50MΩ, at 500VDC	
Safety Standards	安规标准	ETL, FCC, CE	
EMC	电磁兼容标准	EMI: IEC/EN55032, IEC/EN 55035	